

PG9-F ABC

Cartridge
operated

Powder

9 kg

BODY

STEEL

3-pieces mild steel cylinder, wire feed welded. Externally painted with polyester resin.

VALVE

ALUMINUM

Lever operated valve with anodized aluminum body, ensuring high protection against corrosion.

CARTRIDGE

Disposable CO2 cartridge, deep drawn without welds, externally protected by zinc coating and passivation. Cartridge housed in the dip tube.

EXTINGUISHING AGENT

ABC multi-purpose dry extinguishing powder, certified according to EN 615.

HOSE/HORN

The EPDM reinforced rubber hose guarantees perfect flexibility and resistance within the temperature range. Complete with nozzle.

PACKAGING

Single piece cardboard box, robust and suitable for transport.

Temperature ranges

-30° + 60°



On Request



43



233



✓



Configuration

● Standard

○ On request

BRACKET



● Button holed wall bracket PG-M E FG-M



○ TRANSPORT BRACKET PG9-F

PACKAGING



● BOX PG9-F

HOSE RINGS & PROTECTIVE
BASE



○ PROTECTIVE BASE D160 BLACK

Technical data

FIRE RATINGS	43A 233B C	
CHARGE	9 kg ±2%	
MATERIAL	STEEL	
CYLINDER	Manufacturing process	Deep Drawing
	External painting	Polyester Resin
	Corrosion resistance	480 H SECONDO ISO 9227:2017
EXTINGUISHING AGENT	ABC POWDER A32	
PROPELLANT	CO2 - 190GR	
DISCHARGE	Discharge time	~ 23 s
DIMENSIONS	Overall height	658 mm
	Bottle outer diameter	160 mm
	Empty / Charged	4.78 kg / 13.78 kg
PACKING SPECIFICATIONS	Standard packing	1 Pieces cardboard box
	Carton size (B x L x H)	230 x 175 x 775 mm
	Weight per carton	14.36 kg
	Pallet	42 Cartons
	Pallet size (B x L x H)	800 x 1200 x 1511 mm
	Pallet volume	1.45 m3
	Weight per pallet (net/gross)	603 kg / 623 kg



Spare parts list

Description	Code
WALL BRACKET	00.005E.2950.00K0
BURSTING DISC	00.040E.2400.ALK0
ASSEMBLED HOSE	00.040F.2400.00K0
GASKET	00.050E.5000.ORK0
SPINDLE	00.050E.5035.00K0
SHAPED LEVER	00.050E.6000.30K0
VALVE ASSEMBLY WITH YELLOW LEVEL	00.050E.8490.90K0
VALVE ASSEMBLY	00.050E.8500.00K0
TRANSPORT BRACKET	00.050F.2900.00K0
190G CO2 CARTRIDGE	00.050F.3900.01K0
DIP TUBE	00.050F.5900.00K0
CO2 DIP TUBE	00.050F.5951.00K0
White SEAL	00.245E.5030.00K0
SAFETY PIN	00.580E.5020.00K0
BASE Ø160	00.850E.7100.01K0
DADO ESAGONALE CIECO M8; RICAMBI	N000.VT.050.00K0

ANAF Fire Protection

Via del Commercio, 4 - Torre d'Isola (Pavia) - Tel. 0382.4533 Fax. 0382.920279
info@anaf.eu | www.anaf.eu