

CS2-AB

Stored pressure

Carbon Dioxide

2 kg

Temperature ranges

-30°+60°

ANAFGROUP



On Request

BODY

STEEL

Seamless, hot-formed mild steel cylinder. Externally painted with polyester resin.

VALVE

Lever operated valve with nicked brass body. Front-outlet type, provided with burst disk safety relief valve.

EXTINGUISHING AGENT

Carbon dioxide (CO₂). All parts in contact with the extinguishing agent are compatible.

HOSE/HORN

Front horn in polypropylene, providing a perfect diffusion of the extinguishing agent and ensuring a prompt extinguishing and quick cooling of the fire.

PACKAGING

Single piece cardboard box, robust and suitable for transport.



34

Configuration

● Standard

○ On request

BRACKET



● Button holed wall bracket



○ TRANSPORT BRACKET CS2-A

PACKAGING



● CARDBOARD BOX CS2-AB/AM

Technical data

FIRE RATINGS	34B	
CHARGE	2 kg 0 / -5%	
MATERIAL	STEEL	
CYLINDER	Manufacturing process	Deep Drawing
	External painting	Polyester Resin
	Corrosion resistance	480 H SECONDO ISO 9227:2017
EXTINGUISHING AGENT	CO2	
PROPELLANT	CO2	
DISCHARGE	Discharge time	~ 6.5 s
DIMENSIONS	Overall height	570 mm
	Bottle outer diameter	104 mm
WEIGHT	Empty / Charged	4.53 kg / 6.53 kg
PACKING SPECIFICATIONS	Standard packing	1 Pieces cardboard box
	Carton size (B x L x H)	165 x 130 x 632 mm
	Weight per carton	6.93 kg
	Pallet	80 Cartons
	Pallet size (B x L x H)	800 x 1200 x 1600 mm
	Pallet volume	1.54 m3
	Weight per pallet (net/gross)	554 kg / 574 kg



Spare parts list

Description	Code
SAFETY WIRE	00.005A.3220.00K0
TRANSPORT BRACKET	00.707B.2900.00K0
WALL BRACKET	00.752B.2900.10K0
CONE ASSEMBLY	00.754B.2400.00K0
SAFETY PIN	00.754B.5020.00K0
WASHER	00.754B.5070.00K0
DIP TUBE	00.754B.5900.00K0
VALVE ASSEMBLY	00.754B.6950.00K0
DIP TUBE	00.757B.5900.00K0
TRANSPORT BRACKET	00.765B.2900.02K0

ANAF Fire Protection

Via del Commercio, 4 - Torre d'Isola (Pavia) - Tel. 0382.4533 Fax. 0382.920279
info@anaf.eu | www.anaf.eu